

VELOSIT® RD 800

Edging strip with self-adhesive foot



Application fields

VELOSIT RD 800 is a PE foam edge insulation strip with integrated fleece and self-adhesive base. Typical application fields besides others are as follows:

- In combination with VELOSIT floor leveling compounds
- Perfect for renovation
- For decoupling wall and floor
- Safely prevents sound bridges
- For interior and exterior use

Properties

VELOSIT RD 800 is a rot-proof, elastic, fleece-laminated and closed-cell polyethylene foam edge insulation strip with self-adhesive base.

- Self-adhesive - good adhesive strength - prevents running behind
- Moisture resistant
- High adhesion to clean substrates

- Prevents sound bridges and forced voltages
- Safe and simple corner formation
- Perfect fixation to the wall, sets itself up

Application

1.) Substrate preparation

VELOSIT RD 800 is suitable for all standard building substrates which have been properly prepared.

For application, the substrate must be free from separating substances, dry and dust-free. The substrate must be prepared according to the specifications in the respective technical data sheets of the VELOSIT floor levelling compounds.

2.) Processing

Remove the protective film from the adhesive strip and apply the strip to the prepared substrate with press firmly with the self-adhesive foot. The blue side faces the wall. For corner formation, cut the cut the adhesive foot. In connection areas,

VELOSIT RD 800 is butted together seamlessly. Cover the joint areas with a suitable adhesive tape.

Quality features

Color:	blue
Substrate temperature:	5 – 35 °C
Fire rating acc. DIN 4102:	B2

Hersteller

VELOSIT GmbH & Co. KG
Industriepark 5 – 7
32805 Horn-Bad Meinberg
Germany
www.velosit.de

Packaging

VELOSIT RD 800 is supplied in rolls of 20 m.
Thickness: 5 mm, height: 50 mm. There are 5 rolls in the box.

Storage

VELOSIT RD 800 can be stored in cool and dry rooms for approx. 12 months
Place protected against sunlight.

Environment & Safety

Product residues can be disposed of in household waste.

Recommendations

VELOSIT RD 800 must not come into contact with or be reworked with products containing solvents.

VELOSIT RD 800 cannot be removed after application without destroying the material.

VELOSIT RD 800 is only available for professional applicators.

All described product features are determined under controlled laboratory conditions according to the relevant international standards. Values determined under job site conditions may deviate from the stated values.

Please always use the latest version of this data sheet available from our website www.velosit.de.