

according to Regulation (EC) No 1907/2006

VELOSIT GH 311 - B

Revision date: 29.11.2022 Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

VELOSIT GH 311 - B

UFI: 713E-6SN0-YFCW-SCRY

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Curing agent

Uses advised against

The product is intended for professional use.

1.3. Details of the supplier of the safety data sheet

Company name: VELOSIT GmbH & Co. KG

Street: Industriepark 5 - 7

Place: D-32805 Horn-Bad Meinberg

Telephone: +49 (0) 5233/ 9517 - 300 Telefax: +49 (0) 5233/ 9517 - 301

e-mail: info@velosit.de
Contact person: Technical Department
Internet: http://www.velosit.de
Responsible Department: Technical Department

info@velosit.de

1.4. Emergency telephone GBK Gefahrgut Buero GmbH, Tel. +49 (0) 6132 - 84463

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 STOT RE 2; H373

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

diphenylmethane-diisocyanate, isomers and homologues

Signal word: Danger

Pictograms:





Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.



Print date: 02.01.2023

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VELOSIT GH 311 - B	
Revision date: 29.11.2022	Page 2 of 9

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P284 Wear respiratory protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

Special labelling of certain mixtures

EUH204 Contains isocyanates. May produce an allergic reaction.

Restricted to professional users.

As from 24 August 2023 adequate training is required before industrial or professional

use.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

formulated polyisocyanate

Hazardous components

CAS No	Chemical name				
	EC No Index No REACH No				
	Classification (Regulation (EC) No. 1272/2008)				
9016-87-9	diphenylmethane-diisocyanate, isomers and homologues				
	Carc. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT SE 3, STOT RE 2; H351 H332 H315 H319 H334 H317 H335 H373				

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	C No Chemical name		
	Specific Conc. Limits, M-factors and ATE			
9016-87-9		diphenylmethane-diisocyanate, isomers and homologues	> 50 %	
	inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = >9400 mg/kg; oral: LD50 = >10000 mg/kg Skin Irrit. 2; H315: >= 5 - 100 Resp. Sens. 1; H334: >= 0,1 - 100 STOT SE 3; H335: >= 5 - 100			

Further Information

No information available.

SECTION 4: First aid measures

4.1. Description of first aid measures



Print date: 02.01.2023

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VELOSIT GH 311 - B

Revision date: 29.11.2022 Page 3 of 9

General information

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down. Show this safety data sheet to the doctor in attendance.

After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In case of skin irritation, seek medical treatment.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings. Carbon dioxide (CO2). Foam. Extinguishing powder.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Burning releases carbon monoxide, carbon dioxide, oxides of nitrogen and traces of hydrogen cyanide. In the event of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Take up mechanically.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8



Print date: 02.01.2023

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VELOSIT GH 311 - B

Revision date: 29.11.2022 Page 4 of 9

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Wear personal protection equipment (refer to section 8). Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations.

Hints on joint storage

For more information about together and separate storage: refer to TRGS 510

Further information on storage conditions

Recommended storage temperature: 10 - 30 °C

Keep/Store only in original container.

Store in a dry place.

7.3. Specific end use(s)

Further remarks:

Information System of the Professional Association of construction industry see on www.gisbau.de

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Appropriate engineering controls

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles. (EN 166)

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Recommendation to EN 374: For short time use or protection against splashes: Butyl rubber / nitrile rubber (0.4 mm), contaminated gloves should be changed and disposed. Suitable for permanent exposure: Viton gloves (0.4 mm) Break through time> 30 min.

Skin protection

Wear suitable protective clothing. Recommendation: Safety shoes according to EN ISO 20345, long pants and long-sleeved work shirt; with mixing and stirring work additional rubber apron and protective boots according to EN 14605

Respiratory protection

To follow: EN 689 - Methods for determining inhalation exposure In case of inadequate ventilation wear

according to Regulation (EC) No 1907/2006

VELOSIT GH 311 - B

Revision date: 29.11.2022 Page 5 of 9

respiratory protection. Organic vapor filter (Type A) The selection of respirators (EN 14387) must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits (sections 8.1) of the selected respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: brown
Odour: characteristic

Test method

Melting point/freezing point:

Boiling point or initial boiling point and

not determined
not determined

boiling range: Flammability

Solid/liquid: not determined
Lower explosion limits: not determined
Upper explosion limits: not determined

Flash point: > 200 °C DIN EN ISO 2719

Auto-ignition temperature:

Decomposition temperature:

PH-Value:

Viscosity / kinematic:

Water solubility:

No information available.

No information available.

No information available.

No information available.

Solubility in other solvents

No information available.

Dissolution rate:

Partition coefficient n-octanol/water:

Vapour pressure:

not determined

No information available.

No information available.

Density (at 23 °C): ca. 1,13 g/cm³ ISO 2811-2

Relative vapour density:

Particle characteristics:

No information available.

not determined

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

No information available.

Oxidizing properties

No information available.

Other safety characteristics

Evaporation rate:

Sublimation point:

Softening point:

Pour point:

No information available.

not determined
not determined
not determined

Viscosity / dynamic: 160 - 240 mPa·s ISO 2884-1

(at 25 °C)

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

Danger of polymerisation.



according to Regulation (EC) No 1907/2006

VELOSIT GH 311 - B

Revision date: 29.11.2022 Page 6 of 9

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

none

10.5. Incompatible materials

Acid. Oxidizing agents. Water. Alkalis (alkalis). Alcohol

10.6. Hazardous decomposition products

Hydrogen cyanide (hydrocyanic acid).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No. 1272/2008

Acute toxicity

Harmful if inhaled

ATEmix calculated

ATE (inhalation vapour) 12,22 mg/l; ATE (inhalation dust/mist) 1,667 mg/l

CAS No	Chemical name						
	Exposure route Dose S		Species	Source	Method		
9016-87-9	diphenylmethane-diisoo	yanate, isor	mers and hom	ologues			
	oral	LD50 mg/kg	>10000	Rat			
	dermal	LD50 mg/kg	>9400	Rabbit			
	inhalation vapour	ATE	11 mg/l				
	inhalation dust/mist	ATE	1,5 mg/l				

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Contains isocyanates. May produce an allergic reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled. (diphenylmethane-diisocyanate, isomers and homologues)

May cause an allergic skin reaction. (diphenylmethane-diisocyanate, isomers and homologues)

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing cancer. (diphenylmethane-diisocyanate, isomers and homologues)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (diphenylmethane-diisocyanate, isomers and homologues)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (diphenylmethane-diisocyanate, isomers and homologues)

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Further information

Special properties/effects: Over-exposure, especially when spraying coatings containing isocyanate without the necessary precautions, entails the risk of concentration-dependent irritating effects on eyes, nose throat, and respiratory tract. Delayed appearance of the complaints and development of hypersensitivity (difficult breathing, coughing, asthma) are possible. Hypersensitive persons may suffer from these effects even at low isocyanate



according to Regulation (EC) No 1907/2006

VELOSIT GH 311 - B

Revision date: 29.11.2022 Page 7 of 9

concentrations, including concentrations below the UK Workplace Exposure Limit (WEL). Prolonged contact with the skin may cause tanning and irritant effects.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Aquatic toxicity	Dose	[h] [d] Species Source Method		
9016-87-9	diphenylmethane-diisocya	nate, isomers and homo	logues		
	Acute fish toxicity	LC50 >1.000 mg/l	96 h Danio rerio (zebrafish) (OECD 203)		
	Acute crustacea toxicity	EC50 >1000 mg/l	48 h Daphnia Magna (OECD 202)		

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

BCF

CAS No	Chemical name	BCF	Species	Source
9016-87-9	diphenylmethane-diisocyanate, isomers and homologues	<14		

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

The resin reacts with water at the interface forming CO2 and a solid insoluble product with high melting point (polyurea). This reaction is accelerated by surfactants (e.g. detergents) or by watersoluble solvents. Previous experience shows that polyurea is inert and non-degradable.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish

containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish

containing organic solvents or other hazardous substances; hazardous waste



according to Regulation (EC) No 1907/2006

VELOSIT GH 311 - B

Revision date: 29.11.2022 Page 8 of 9

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances; hazardous waste

Contaminated packaging

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself. Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 56, Entry 74

2004/42/EC (VOC): VOC content (g/L), delivery state: < 500

Subcategory according to Directive Two-pack reactive performance coatings for specific end use such as

2004/42/EC: floors - Solvent-borne coatings, VOC limit value: 500 g/l

Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III)

(SEVESO III):

Additional information

Prohibition/Restriction:

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII): 3, 56, 74

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). None of the components are listed (=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV): not applicable

REACH Information: All substances contained in our Products are preregistered or registered by our upstream suppliers, and/or preregistered or registered by us, and/or excluded from the regulation, and/or exempted from the registration.

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.



according to Regulation (EC) No 1907/2006

VELOSIT GH 311 - B

Revision date: 29.11.2022 Page 9 of 9

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008

Classification	Classification procedure
Acute Tox. 4; H332	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Resp. Sens. 1; H334	Calculation method
Skin Sens. 1; H317	Calculation method
Carc. 2; H351	Calculation method
STOT SE 3; H335	Calculation method
STOT RE 2; H373	Calculation method

Relevant H and EUH statements (number and full text)

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
EUH204	Contains isocyanates. May produce an allergic reaction.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)